### DATA SHEET.

# RIDE-ON SCRUBBER DRYER. ARA 66 BM 70





G. Staehle GmbH u. Co. KG Mercedesstrasse 15 D 70372 Stuttgart Telefon +49 (0) 7 11/95 44-960 Telefax +49 (0) 7 11/95 44-941 export@columbus-clean.com www.columbus-clean.com



## **ERGONOMIC. EFFICIENT.** AND EXCEPTIONALLY COMPACT. ARA 66 BM 70

- With a capacity of 70 litres, this ride-on scrubber dryer can perform efficient operations, even - and especially - in hospitals, supermarkets and other small buildings even with cramped and heavily-furnished areas.
- () The standard electronic water dosing system allows exact water supply following the needs of different cleaning tasks.
- O Whether the operator is just 155 cm or 195 cm tall, the long seat allows everyone to find the right position to work fatiguefree and relaxed.
- () Fast, easy and hygienic changing of brushes and pad holders: the brushes and pad holders do not only spin-off with the press of a button, they also spin-on automatically.

- Fresh water can be filled up in an instant - via the integrated, industry-standard system connector or via the large filling opening.
- HACCP hygiene standards: the solution and recovery tank have inspection openings and can be thoroughly cleaned, the lid seals can be removed without tools.
- O Robust mechanics: simple operating switches to turn the machine on and off and for forward and backward movements. Mechanical lowering of brushes and squeegee. • Just 138 cm long and 85 cm
- O Powerful traction motor and rearwheel drive allow scrubbing on inclines of up to 12%.
- Optional: Various tyre variants for optimum adaption to diverse working conditions.

- O Easy service: the seat can be lifted up to provide free access to batteries and components.
- The arch-shaped squeegee tool adapts to the movements of the machine and will perfectly pick up without leaving any waste water even on tight turns.
- Operators can act quickly and flexibly thanks to a low step height, an open cockpit on both sides and a spacious footwell.
- wide, the ride-on scrubber dryer fits into all standard lifts and and can easily negotiate narrow checkout areas.



# MECHANICS INSTEAD OF ELECTRONICS. AND LOTS OF USEFUL FEATURES.


- Optional: silent-version that operates at only 59 dB(A) and a security-kit for advanced security when used in facilities that are open to the public.
- () Environmentally friendly: the optional chemical dosage provides for a consistently high cleaning level with a low consumption of cleaning products. The 8 litres chemical tank can be removed without tools.
- A faster clean: the area covered every hour is up to 600 m² larger compared to the performance of walk-behind scrubber dryers of the same size.
- O DEKRA certified.
- O And: made in Germany.



Pull-out filter for large debris



With small operator



**Emergency stop button** 



With tall operator





#### ARA 66 BM 70

| LxBxH                       | 1380 x 680 x 1170 mm |
|-----------------------------|----------------------|
| Working width               | 660 mm               |
| Suction width               | 850 mm               |
| Theoretical coverage max.   | 3960 / 4620 m²/h*    |
| Noise level                 | 63/59** dB(A)        |
| Empty weight                | 187 kg               |
| Operating weight (180 Ah 5) | 456 kg               |

#### **BATTERIES/ELECTRICAL DATA**

| Rated voltage       | 24 V     |
|---------------------|----------|
| Power max.          | 1690 W   |
| Number of batteries | 4        |
| Capacity wet        | 200 Ah 5 |
| Capacity gel        | 180 Ah 5 |

#### TANK

| Solution tank capacity | 70 l |
|------------------------|------|
| Recovery tank capacity | 80 I |

#### SUCTION

| Low pressure max. | 110 mbar |
|-------------------|----------|
| Air flow max.     | 32 l/s   |

#### TRACTION

| Power max. | 750 W      |
|------------|------------|
| Speed max. | 6 / 7 km/h |

#### BRUSHES AND PAD HOLDERS

| Number         | 2       |
|----------------|---------|
| Speed          | 180 rpm |
| Brush pressure | 30 kg   |

\*available with 6 km/h or 7 km/h

<sup>\*\*</sup>silent version, optional.

