DATA SHEET.

SCRUBBER DRYER. RA 43|B20





G. Staehle GmbH u. Co. KG Mercedesstrasse 15 D 70372 Stuttgart Telefon +49 (0) 7 11/95 44-960 Telefax +49 (0) 7 11/95 44-941 export@columbus-clean.com www.columbus-clean.com

columbus

COMPACT. PROFESSIONAL. 20 LITRES.

RA 43 B 20

- With lots of handy details and long Work close to edges and get operating intervals, the RA 43IB 20 shows its class in clinics, homes for the elderly, schools, shops, swimming and leisure centres, to name but a few locations - where O For easy access to batteries and compactness and manoeuvrability are decisive.
- () A uniaxial construction with biaxial comfort: the transportation wheel () Hygiene in accordance with is lowered by foot pedal. This means the machine can easily be rolled to the area where it is to be used, the pressure on the brush is relieved during storage and the brush can dry properly.
- underneath objects without difficulty: the brush head protrudes out 5 cm to the side.
- motors, the recovery tank can be removed quickly and without
 - HACCP: the recovery tank can be thoroughly and effortlessly cleaned and disinfected via the large opening.
 - O DEKRA and EUnited tested and certified.









Self explaining control panel



Quick-Stopp as standard

- The working width of 43 cm provides extended fields of applications and greater area coverage in the 20-litre class.
- Quick-Stopp as standard: the brush motor and water supply stop automatically when you let go the handle.

The recovery tank can be easily tilted and then comfortably and precisely emptied down to the last drop, through the drain hose and straight into the sink – up to a height of 50 cm.



A CLASS OF ITS OWN.

- Save space when transporting and storing: simply fold the handle forward and remove the squeegee tool.
- For flexible work in cramped areas, the handle can be put into the right position in one movement.
- The arch-shaped squeegee tool with Optional: the silent version with its patented mounting system actively adjusts to the movements of the machine and thus picks up all O noBAC® version optional: antidirt, even in corners.
- The brush or pad holder are positioned and dropped automatically: fast, comfortable and hygienic.
- The standard version with its 10 A integrated charger and powerful batteries allows for up to 2.5 hours of continuous operation.

- a noise level of just 59 dB(A).
- bacterial tanks for every kind of sites with stringent hygiene requirements according to HACCP concept or following hygiene plan.
- O And: made in Germany.





RA 43 B 20

LxWxH	800 x 530 x 790 mm
Working width	430 mm
Suction width	730 mm
Theoretical coverage max.	1720 m²/h
Noise level	63/59* dB(A)
Empty weight	56 kg
Operating weight (76 Ah 5)	134 kg

BATTERIES/ELECTRICAL DATA

Rated voltage	24 V
Power max.	950 W
Number of batteries	2
Capacity gel	76 Ah 5

TANK

Solution tank capacity	20
Recovery tank capacity	23

SUCTION

Low pressure max.	110 mbar
Air flow max.	32 l/s

BRUSHES AND PAD HOLDERS

Number	1
Speed	180 rpm
Brush pressure	30 kg

*silent version, optional.